

AXIS M3115-LVE Network Camera

Affordable flat-faced 1080p dome with IR

AXIS M3115-LVE is an affordable, flat-faced dome designed to suppress light reflections. This compact, IK08-rated camera features a wide-angle view in HDTV 1080p video. It includes Forensic WDR, Lightfinder and built-in IR illumination for sharp video with clear colors even in challenging light or complete darkness. Additionally, it offers flexible installation for both indoor and outdoor surveillance. And, with its 3-axis camera-angle adjustment, it can be easily leveled and directed. It features enhanced security functionality, and Axis Zipstream with support for H.264/H.265 significantly reduces bandwidth and storage requirements without compromising image quality.

- > [HDTV 1080p video quality](#)
- > [Forensic WDR, Lightfinder and IR illumination](#)
- > [Flat-faced design suppressing light reflections](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [Signed firmware and secure boot](#)



AXIS M3115-LVE Network Camera

Camera		Event actions	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text
Image sensor	1/2.9" progressive scan RGB CMOS	Data streaming	Event data
Lens	2.8 mm, F2.0 Horizontal field of view: 105° Vertical field of view: 58° Fixed iris, Fixed focus, IR corrected	Built-in installation aids	Pixel counter, adjustable IR-illumination intensity
Day and night	Automatically removable infrared-cut filter	General	
Minimum illumination	Color: 0.17 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0 0 lux with IR illumination on	Casing	IP66- and NEMA 4X-rated, IK08 impact-resistant casing Encapsulated electronics and captive screws (Torx 10) Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner
Shutter speed	1/33500 s to 2 s	Sustainability	PVC free
Camera angle adjustment	Pan: ±180° Tilt: 0° to 60° (0° = lens directed at a right angle to camera base) Rotation: ±95° Can be directed in any direction and see the wall/ceiling	Memory	512 MB RAM, 512 MB Flash
Video		Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical: 3.7 W, Max.: 7 W
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	Connectors	RJ45 10BASE-T/100BASE-TX PoE Audio and I/O connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology
Resolution	1920x1080 to 160x90	IR illumination	Power-efficient, long-life 850 nm IR LED. Range of reach 20 m (65 ft) or more depending on the scene
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	Storage	Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	Operating conditions	-30 °C to 50 °C (-22 °F to 122 °F) Start-up temperature: -20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–100% RH (condensing)
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	Storage conditions	-40°C to 65°C (-40°F to 149 °F) Humidity 5–95% RH (non-condensing)
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, Forensic WDR: up to 120 dB depending on scene, fine tuning of low-light behavior, defogging, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270° including Corridor Format	Approvals	EMC EN 55024, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, ICES-3(A)/NMB-3(A), VCCI Class A Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27 IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X Safety IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IEC/EN 62471, IS 13252 Network NIST SP500-267, IPv6 USGv6
Pan/Tilt/Zoom	Digital PTZ	Dimensions	Height: 94 mm (3.7 in) ø 101 mm (4.0 in)
Audio		Weight	390 g (0.85 lb)
Audio input/output	Two-way audio connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	Included accessories	Installation Guide, Windows decoder 1-user license, Torx® L-key, Connector guard, Cable gasket
Network		Optional accessories	AXIS T94B02D Pendant kit, AXIS T94B01P Conduit Back Box, AXIS T94B02M J-Box/Gang Box Plate, AXIS TM3807 Black Casing, Axis Mounts, AXIS Surveillance microSDXC™ Card, AXIS Weathershield Kit C, AXIS T61 Audio and I/O Interface Series For more accessories, see axis.com
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, Digest authentication, User access log, Centralized Certificate Management, brute force delay protection, signed firmware, secure boot	Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on axis.com/vms
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, MQTT, Syslog	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
System integration		Warranty	5-year warranty, see axis.com/warranty
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.	a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).	
Analytics	Included AXIS Video Motion Detection, tampering alarm Supported AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	Event triggers	
Event triggers	Analytics, Edge storage events, Virtual inputs through API	Environmental responsibility:	

