

AXIS Q1910/-E Thermal Network Cameras

Reliable detection in dark and challenging conditions



- > Thermal imaging for IP-Surveillance
- > Outdoor-ready model with window heater
- > Power over Ethernet
- > Multiple H.264 streams with individual palettes
- > Intelligent video capabilities

AXIS Q1910/-E Thermal Network Cameras are a perfect complement to any network video system that needs to secure an area 24 hours a day, seven days a week. The cameras use thermal imaging, which allows users to detect people, objects and incidents in complete darkness and difficult conditions such as smoke, haze, dust and light fog.

AXIS Q1910 is intended for indoor environments, while AXIS Q1910-E is an out-of-the-box, outdoor-ready model that is designed to withstand harsh weather conditions. AXIS Q1910-E comes with a built-in heater for the window.

Installation of both products is made easy and cost-effective with Power over Ethernet (IEEE 802.3af), which eliminates the need for power cables.

AXIS Q1910/-E cameras support H.264 video compression, which reduces bandwidth usage and storage needs by up to 80% compared to Motion JPEG. The cameras provide multiple, individually configurable video streams in H.264 and Motion JPEG. Each stream can have its own color palette setting.

AXIS Q1910/-E are the first thermal cameras on the market with two-way audio support, which allows the user to communicate with visitors and intruders.

Since thermal cameras are less sensitive to problems with light conditions and normal shadows, they can achieve higher accuracy than conventional cameras in most intelligent video applications. AXIS Q1910/-E cameras offer motion detection, audio detection, and detection of tampering attempts. The cameras also provide capacity for third-party analytics modules, including support for AXIS Camera Application Platform.

AXIS Q1910/-E cameras support ONVIF for interoperability between network video products.




Technical specifications – AXIS Q1910/-E Thermal Network Cameras

Camera		System integration													
Models	Indoor: AXIS Q1910 Outdoor: AXIS Q1910-E	Application Programming Interface	Open API for software integration, including the ONVIF specification available at www.onvif.org , as well as VAPIX® and AXIS Camera Application Platform from Axis Communications, specifications available at www.axis.com Support for AXIS Video Hosting System (AVHS) with One-Click Camera connection												
Image sensor	Uncooled Micro bolometer 160x120, pixel size: 25 µm, spectral range: 8-14µm	Intelligent video	Video motion detection, active tampering alarm, audio detection. Support for AXIS Camera Application Platform enables installation of additional applications												
Lens	f 13 mm, F1.25. Angle of view, horizontal: 17°	Alarm triggers	Intelligent video and external input												
Detection range	<table border="1"> <thead> <tr> <th></th> <th>Human 1.8 x 0.5 m</th> <th>Vehicle Vehicle: 1.4 x 4.0 m</th> </tr> </thead> <tbody> <tr> <td>Detection (1.5 pixels on target)</td> <td>260 m / 284 yd.</td> <td>800 m / 875 yd.</td> </tr> <tr> <td>Recognition (6 pixels on target)</td> <td>65 m / 71 yd.</td> <td>200 m / 219 yd.</td> </tr> <tr> <td>Identification (12 pixels on target)</td> <td>30 m / 33 yd.</td> <td>100 m / 109 yd.</td> </tr> </tbody> </table>		Human 1.8 x 0.5 m	Vehicle Vehicle: 1.4 x 4.0 m	Detection (1.5 pixels on target)	260 m / 284 yd.	800 m / 875 yd.	Recognition (6 pixels on target)	65 m / 71 yd.	200 m / 219 yd.	Identification (12 pixels on target)	30 m / 33 yd.	100 m / 109 yd.	Alarm events	File upload via FTP, HTTP and email; notification via email, HTTP and TCP; external output activation
	Human 1.8 x 0.5 m	Vehicle Vehicle: 1.4 x 4.0 m													
Detection (1.5 pixels on target)	260 m / 284 yd.	800 m / 875 yd.													
Recognition (6 pixels on target)	65 m / 71 yd.	200 m / 219 yd.													
Identification (12 pixels on target)	30 m / 33 yd.	100 m / 109 yd.													
	Calculated with Johnson's criteria. The detection range varies in different weather conditions.	General													
Sensitivity	NETD < 100 mK	Casing	AXIS Q1910: Zinc chassis AXIS Q1910-E: IP66-rated aluminum casing and a germanium window												
Video		Processor and memory	128 MB RAM, 128 MB Flash												
Video compression	H.264 (MPEG-4 Part 10/AVC) Motion JPEG	Power	Power over Ethernet IEEE 802.3af Class 3 8-20 V DC / 20-24 V AC 50-60 Hz AXIS Q1910: max 10 W, max 15 VA AXIS Q1910-E: max 13 W, max 18 VA Power supply not included												
Resolutions	Sensor is 160x128. Image can be scaled up to 720x576 (D1) and to standard VGA resolutions	Connectors	RJ-45 10BASE-T/100BASE-TX PoE, terminal block for power, terminal block for two configurable inputs/outputs 3.5 mm mic/line in, 3.5 mm line out RS-422/RS-485 Terminal block for AXIS Q1910/-E heater												
Frame rate	8.33 fps	Local storage	SD/SDHC memory card slot (card is not included)												
Video streaming	At least 5 streams in H.264 and Motion JPEG: simultaneous, individually configured streams in max. resolution at 8.33 fps Controllable frame rate and bandwidth. VBR/CBR H.264	Operating conditions	Shock resistance: 70 g shock pulse with a 11 ms half-sine profile Vibration resistance: 4.3 g random vibration for 8 hours (three axes) AXIS Q1910: -40 °C to 50 °C (-40 °F to 122 °F), humidity 20-80% RH (non-condensing) AXIS Q1910-E: -40 °C to 50 °C (-40 °F to 122 °F), IP66												
Image settings	Compression, brightness, exposure control, rotation, mirroring of images, text and image overlay, privacy mask, multiple palettes	Approvals	EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 50121-4, EN 61000-6-1, EN 61000-6-2, EN 60950-1, FCC Part 15, Subpart B, Class B, VCCI, Class B ITE, C-tick AS/NZS CISPR 22, ICES-003, Class B, IP66												
Audio		Weight	AXIS Q1910: 990 g (2.18 lb.) AXIS Q1910-E: 3520 g (7.76 lb.)												
Audio streaming	Two-way, half duplex	Included accessories	Connector kit, Installation Guide, Windows decoder 1-user license AXIS Q1910-E: wall mount bracket, 5 m (16 ft.) Ethernet cable												
Audio compression	AAC LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz Configurable bit rate	Optional accessories	Wall bracket accessories Pan/tilt motor AXIS Camera Station and video management software from Axis' Application Development Partners. For more information, see www.axis.com/products/video/software/												
Audio input/output	AXIS Q1910: Built-in microphone, external microphone or line input, line output AXIS Q1910-E: External microphone or line input, line output														
Network															
Security	Password protection, IP address filtering, HTTPS* encryption, IEEE 802.1X* network access control, digest authentication, user access log														
Supported protocols	IPv4/v6, HTTP, HTTPS*, QoS Layer 3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS. Wide range of PT heads supported (drivers available for download at www.axis.com).														

* This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org)

More information is available at www.axis.com

Dimensions: AXIS Q1910 Network Camera



Dimensions: AXIS Q1910-E Network Camera including wall mount bracket with internal cable channel

