

# AXIS Q1941-E PT Mount Thermal Network Camera

Wide thermal coverage with pan/tilt flexibility

The bullet-style, outdoor-ready AXIS Q1941-E PT Mount offers the possibility of mounting the camera on a pan/tilt motor to increase installation flexibility. The broad range of lenses make it easy to detect and verify people, objects and incidents from pitch dark areas to a sunlit parking lot. A noise filter gives improved thermal image contrast while keeping noise levels low, without adding blur and ghost effects. AXIS Q1941-E PT Mount withstands harsh weather conditions and has a built-in heater for the window. Additionally, it offers Power over Ethernet and has a microSD card slot.

- > [PT mount-ready](#)
- > [Powerful performance for video analytics](#)
- > [Electronic Image Stabilization](#)
- > [Axis Zipstream](#)



# AXIS Q1941-E PT Mount Thermal Network Camera

<b>Models</b>	AXIS Q1941-E PT Mount 7 mm, 13 mm, 19 mm, 35 mm, 60 mm	<b>Built-in installation aids</b>	Pixel counter
<b>Camera</b>			
<b>Image sensor</b>	Uncooled Micro bolometer 384x288, pixel size: 17 µm Spectral range: 8-14 µm	<b>General</b>	
<b>Lens</b>	Athermalized 7 mm Horizontal field of view: 55°, F1.18 Near focus distance: 1.3 m (4.3 ft) 13 mm Horizontal field of view: 28°, F1.0 Near focus distance: 5.3 m (17 ft) 19 mm Horizontal field of view: 19.4°, F1.23 Near focus distance: 9.2 m (30 ft) 35 mm Horizontal field of view: 10.5°, F1.2 Near focus distance: 33 m (108 ft) 60 mm Horizontal field of view: 6.2°, F1.25 Near focus distance: 91 m (300 ft)	<b>Casing</b>	IP66- and NEMA 4X-rated Metal casing (aluminum) with integrated dehumidifying membrane and a germanium window Color: White NCS S 1002-B
<b>Sensitivity</b>	NETD < 70 mK	<b>Sustainability</b>	PVC free
<b>Pan/Tilt</b>	Preset positions, guard tour, driver selection, control queue	<b>Memory</b>	512 MB RAM, 256 MB Flash
<b>Video</b>			
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles Motion JPEG	<b>Power</b>	Power over Ethernet IEEE 802.3af/802.3at Type 1 Class 3 Typical 4.8 W, max 11.8 W 8-28 V DC, typical 6.6 W, max 13 W 20-24 V AC (50/60 Hz), typical 11 VA, max 19 VA Power supply not included.
<b>Resolution</b>	Sensor is 384x288. Image can be scaled up to 768x576.	<b>Connectors</b>	RJ45 10BASE-T/100BASE-TX PoE Terminal block for power RS485/RS422 for pan/tilt control
<b>Frame rate</b>	Up to 8.3 fps and 30 fps	<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Video streaming</b>	At least three H.264 and Motion JPEG streams, simultaneous and individually configured in max. resolution in full frame rate Axis Zipstream technology in H.264 Controllable frame rate and bandwidth VBR/ABR/MBR H.264	<b>Operating conditions</b>	-40 °C to 60 °C (-40 °F to 140 °F) Humidity 10-100% RH (condensing) De-icing capability, compliant to MIL-STD-810F Method 521.3
<b>Image settings</b>	Compression, brightness, sharpness, contrast, exposure zone, text and image overlay, privacy mask, mirroring of images, electronic image stabilization, multiple palettes Rotation: 0°, 180°	<b>Storage conditions</b>	-40 °C to 70 °C (-40 °F to 158 °F)
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware	<b>Approvals</b>	EMC EN 55022 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR22 Class A KCC KN32 Class A, KN35 Safety EN 62368-1 Environment EN 50581, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6 Class 4M4, IEC 60068-2-27, IEC 60068-2-52, IEC 60721-3-4 Class 4K3, MIL-STD-810F Method 521.3 IEC 60529 IP66 Network NIST SP500-267
<b>Supported protocols</b>	IPv4, IPv6, USGv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP, MQTT	<b>Dimensions</b>	309 x 105 mm (12 3/16 x 4 1/8 in)
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile G and ONVIF <sup>®</sup> Profile S specification at <a href="http://onvif.org">onvif.org</a>	<b>Weight</b>	7/13/19 mm: 1800 g (4.0 lb) 35 mm: 1900 g (4.2 lb) 60 mm: 2000 g (4.4 lb)
<b>Analytics</b>	<b>Included</b> AXIS Video Motion Detection, AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard, shock detection <b>Supported</b> AXIS Perimeter Defender Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>	<b>Included accessories</b>	Torx <sup>®</sup> T20 screw driver, Terminal block connector Installation Guide, Windows <sup>®</sup> decoder 1-user license
<b>Event triggers</b>	Analytics, temperature, external input, time scheduled, edge storage events PTZ preset	<b>Optional accessories</b>	Axis PoE Midspans, AXIS T8129 PoE Extender, AXIS T8640 PoE+ over Coax Adapter Kit, AXIS T8604 Media Converter Switch AXIS T8415 Wireless Installation Tool AXIS T8310 Control Board For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Event actions</b>	File upload: FTP, SFTP, HTTP, HTTPS network share, email Notification: email, HTTP, HTTPS and TCP, SNMP trap External output activation Video recording to edge storage Pre- and post-alarm video buffering PTZ preset, guard tour, overlay text	<b>Video management software</b>	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>
<b>Data streaming</b>	Event data	<b>Languages</b>	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
		<b>Warranty</b>	5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
		<b>Export control</b>	This product is subject to export control regulations. You should always consult and comply with the regulations of the appropriate local export control authorities.

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)