

TECNOVIDEO

CCTV SYSTEMS AND ACCESSORIES

SECIRLED SERIES

SECURITY IR LED ILLUMINATOR

- ALUMINUM CONSTRUCTION
- INFRARED LED TECHNOLOGY, 850nm
- BEAM PATTERNS 25° OR 60°
- WEATHERPROOF STANDARD IP66/IP67



TECHNICAL SPECIFICATIONS

GENERAL & MECHANICAL

Dimensions	See drawings next page
Operating Temperature	-40° +60°C (-40° +140° F)
Construction	Aluminum + Polycarbonate cover
Finish	Black anodized
Mounting	See drawings next page
Cable entries	1mt cable preassembled
Weight	Unit: 0.9kg; Package: 1.5kg

ELECTRICAL

Available voltages	24VAC (+/-10%)
Activation	No external activation, only power on/power off
Max power consumption	24W

LED ILLUMINATOR

LED	SMD LED
Wavelength	850nm
Beam patterns	25° or 60°

CERTIFICATIONS

Ingress Protection	IP66/IP67 (EN 60529)
EMC	EN50130-4; EN55035 ; EN/IEC61000-6-2; EN/IEC61000-6-4
LVD	EN 60950-1 ; EN 60950-22
RoHS	2011/65/EU + 2015/863/EU (RoHS 3)
WEEE	2012/19/EU

MODELS

SECIRLED25/24	Aluminum Infrared LED illuminator. 25° beam pattern, 24VAC
SECIRLED60/24	Aluminum Infrared LED illuminator. 60° beam pattern, 24VAC

ACCESSORIES

PSU150	Indoor 230VAC/24VAC power supply
---------------	----------------------------------

DIMENSIONS

The dimensions in the technical drawings are in millimetres.

